SPECIAL APPLICATION MAGNETIC DRILLING SOLUTIONS









ST® 50A

The AirBeast® 50A is ideal for hazardous environments such as oil drilling platforms, mining, shipbuilding and petrochemical industries. A pneumatic drive and permanent magnetic base eliminates the need for electric power.

- Strong permanent magnetic base.
- 2 morse taper twist drill capacity.
- ATEX-approved materials. Safe for use in Ex zones and environments with hazardous, flammable, or combustible vapors, liquids, dust, or residues.
- Enhanced mechanical safety lock prevents accidental motor activation.
- Permanent magnetic base with V-shaped prismatic foot. Enables drilling on pipes from 250 mm upwards.
- Innovative sliding ON/OFF pneumatic motor switch. Provides compressed air to the pneumatic motor.



AirBeast® 50A



Model	AIRBEAST 50 ATEX
Spindle	2MT (19 mm shank)
Maximum drilling capacity with annular cutter	50 mm (2")
Maximum drilling capacity with twist drill	23 mm (13/16")
Maximum depth of cut	50 mm (2")
Max Stroke	150 mm
Air consumption	1400 I/min (50 CFM)
Pressure	6 Bar (87 psi)
Air Connection	CEJN 410 DN 10.4 R $3/8$ " BSPT fitting for quick coupling
RPM (under load)	2 Fixed Speeds 290 / 190 RPM
Magnet Deadlift	968 kg on 1" Plate (9500 N)
Overall Dimensions	487 mm x 188 mm x 790 mm
Magnetic Base dimensions	90 mm x 192.5 mm x 66.5 mm
Noise Level	< 90dB
Vibration Level	< 2.5 m/s2
Weight	24.5 kg
Shipping Weight	42 kg
Shipping Dimensions	600 mm x 800 mm x 800 mm
Part no	DRILL-AIR50A

床(ce



Part no' DRILL-AIR50A



Safety conscious separate magnet and motor switch gear prevents accidental start up.



50 mm Ø cutter capacity.



23 mm, 2MT solid drill capacity.



